



ITEM #BS118664



SLIMLINE™

THE ODOROX® SLIMLINE™ UNIT IS DESIGNED FOR CRITICAL GERM / VIRUS ELIMINATION. IT PROCESSES A HEAVY CONCENTRATION OF HYDROXYL PARTICLES USING AMBIENT MOISTURE FROM THE AIR.

ADDITIONAL USES INCLUDE:

- *Fire and Water Damage*
- *Toxic Odors*
- *Volatile Organic Compounds (VOC)*
- *Mold*

The **SLIMLINE™** unit is equipped with a variable speed fan control and a washable filter. The built-in fan only draws 1.4 amps and is adjustable up to 500 cfm. It is perfect for small buses, medical offices, classrooms, commercial offices, etc.

Each unit can treat UP TO 1000 SQ.FT.

SPECIFICATIONS:

- **Dimensions:** 18" x 5.2" x 25"
(457mm x 133mm x 635mm)
- **Weight:** 17.6lbs, 7.9kg
- **Voltage:** 120V @ 60Hz / 220V @ 50/60Hz
- **Power:** 170 Watts (Max)
- **Control:** Speed Control
- **Mobility:** Handle / Stand Brackets
- **Finish:** Black or Beige powder coat
- **Noise Level:** <55dBa
- **Number of Optics:** 1
- **Air Inlet / Outlet:** Louvered panel
- **Fans & Rating:** One 500 CFM
- **Fan Speed:** 200ft³/m
(based on 230VAC, 50Hz fan set on high speed)
- **Filters:** One, 5" x 12.5" x 0.25"
(127mm x 317.5mm x 6.4mm), Washable
- **Certification:** Meets Canada / US – CSA & UL Standards, Meets CE, REACH, & RoHS, Residual O₃ / Non-accumulative



GREEN TECHNOLOGY AT WORK™



ITEM #BS118662



BOSS™

THE ODOROX® BOSS™ UNIT IS DESIGNED FOR CRITICAL GERM / VIRUS ELIMINATION. IT PROCESSES A HEAVY CONCENTRATION OF HYDROXYL PARTICLES USING AMBIENT MOISTURE FROM THE AIR.

ADDITIONAL USES INCLUDE:

- *Fire and Water Damage*
- *Toxic Odors*
- *Volatile Organic Compounds (VOC)*
- *Mold*

The **BOSS™** unit is equipped with a selector switch for 1 or 2 hydroxyl generating optics and a washable filter. The built-in fan only draws 1.9 amps and is adjustable from 250 to 500 cfm. Using the fan's low setting treats small areas such as nurse's offices, buses, small classrooms, offices, etc. The high setting to treats larger areas such as locker rooms, large classrooms, conference rooms, etc.

Each unit can treat UP TO 2000 SQ.FT.

SPECIFICATIONS:

- **Dimensions:** 18.25" x 12.1" x 25.25"
(464mm x 308mm x 641mm)
- **Weight:** 39lbs, 17.7kg
- **Voltage:** 120v @ 60Hz / 220V @ 50/60 Hz
- **Power:** 230 Watts (max)
- **Control:** Speed Control / Selector Switch
- **Meter:** 1/10 quartz hour meter
- **Mobility:** Handle / Rubber feet / Optional wheeled cart
- **Finish:** Bronze powder coat
- **Noise Level:** <55 dBA
- **Number of Optics:** 2
- **Air Inlet / Outlet:** Louvered Panel
- **Fans & Rating:** One 629 CFM
- **Fan Speed :** 230 ft³/m
(based on 230VAC, 50Hz fan set on high speed)
- **Filter:** One 9" x 18" x 1"
(228.6mm x 457.22mm x 25.4mm), Washable
- **Certification:** Meets Canada / US – CSA Meets CE, REACH, & RoHS, Residual O₃ / Non-accumulative